



MINERAL TURPENTINE

Mineral Turpentine

DESCRIPTION

Hydrocarbon solvent specifically designed for use in many paint formulations and associated thinners. **Mineral Turpentine** is one of the most widely used hydrocarbon solvents as it combines good solvency with controlled evaporation. Use **Mineral Turpentine** for thinning paints, linseed oil, waxes and polishes, metal cleaning and clean-up of brushes and equipment after painting.

FEATURES

Mid-range evaporation rate.

Good solvency for oil, grease, wax and silicone.

Relatively low cost.

No residue on drying.

Versatility – **Mineral Turpentine** can be included in any formulation where controlled evaporation is required and is miscible with all other organic solvents.

Solvency – **Mineral Turpentine** has good solvency for greases, oils, and general dirt – as well as for alkyd resins in enamel paints.

PACKAGING

Mineral Turpentine is available in bulk, IBCs (1500 litre bulk containers), drums, 20 litre containers and 4 x 4 litre and 12 x 1 litre cartons.

SAFETY

Please consult the MSDS on **Mineral Turpentine** before use.

The information and recommendations contained herein are based on data believed to be correct at this time. However, no guarantee of any kind, expressed or implied is made with respect to the information contained herein.

Typical Characteristics

Appearanceclear, pale-yellow liquid
 Specific Gravity.....0.81
 Flash Point.....>31°C
 Boiling Point..... 145–200°C
 Aromatic Content..... ~47%

 **MSDS** available

QUEENSLAND
Tel +61 7 3308 5200
Fax +61 7 3308 5201

NEW SOUTH WALES
Tel +61 2 8709 9600
Fax +61 2 9791 5066

VICTORIA
Tel +61 3 9408 4144
Fax +61 3 9408 4155

SOUTH AUSTRALIA
Tel +61 8 8222 1333
Fax +61 8 8260 7883

WESTERN AUSTRALIA
Tel +61 8 9352 3000
Fax +61 8 9352 3033